

OSHA Regulations Impact

Area of emphasis	Rule number	Description of impactful changes or additional regulations compared to current ETA regulations
Site	1910.142(a)(1)	(CHANGE) OSHA requires that they shall not be subject to periodic flooding, nor located within 200 feet of swamps, pools, sink holes, or other surface collections of water unless such quiescent water surfaces can be subjected to mosquito control measures.
Site	1910.142(a)(2)	(NEW RULE) OSHA states that the principal camp shall be at least 500 feet from any area in which livestock is kept.
Shelter	1910.142(b)(2)	(CHANGE) OSHA increases square footage of floor space for each occupant from 40' to 50' for bunk beds.
Shelter	1910.142(b)(3)	(CHANGE) OSHA requires suitable storage facilities in every sleeping room. Beds or similar facilities shall be spaced not closer than 36 inches both laterally and end to end, and elevated at least 12 inches from the floor. If double bunk beds are used, they shall be spaced not less than 48 inches both laterally and end to end.
Shelter	1910.142(b)(5)	(NEW RULE) OSHA Mandates all wooden floors shall be elevated not less than 1 foot above the ground level at all points to prevent dampness and to permit free circulation of air beneath.
Shelter	1910.142(b)(7)	(CHANGE) OSHA increases the openable window area from 45% to 50%
Shelter	1910.142(b)(9)	(CHANGE) OSHA increases the square footage of rooms where workers cook, live and sleep from 60' to 100' per person.
Water	1910.142(c)(2)	(NEW RULE) OSHA requires adequate water supply which is capable of delivery 35 gallons per person per day at a peak rate of 2 1/2 times the average hourly demand.
Water	1910.142(c)(3)	(CHANGE) OSHA requires the water distribution lines shall be capable of supplying water at a normal operating pressure to all fixtures for simultaneous operation
Water	1910.142(c)(4)	(NEW RULE) OSHA states where water under pressure is available, one or more drinking fountains shall be provided for each 100 occupants or fraction thereof
Toilet Facilities	1910.142(d)(2)	(NEW RULE) OSHA states each toilet room shall be located so as to be accessible without any individual passing through any sleeping room. Toilet rooms shall have a window not less than 6 square feet in area opening directly to the outside area or otherwise be satisfactorily ventilated. All outside openings shall be screened with 16-mesh material. No fixture, water closet, chemical toilet, or urinal shall be located in a room used for other than toilet purposes.
Toilet Facilities	1910.142(d)(3)	(CHANGE) OSHA requires that a toilet room shall be located within 200 feet of each <u>sleeping room</u> versus 200 feet from <u>living unit</u> in ETA regs AND OSHA increase the allowable distance of privies to sleeping, dining, lunch or kitchen area from 50' to 100 ft
Toilet Facilities	1910.142(d)(6)	(CHANGE) OSHA states that urinals shall be provided on the basis of one unit or 2 linear ft of urinal for each 25 men. Urinals shall be provided with adequate water flush
Toilet Facilities	1910.142(d)(8)	(CHANGE) OSHA states each toilet room shall be lighted naturally or artificially by a safe type of lighting at <u>all hours of the day and night</u>
Toilet Facilities	1910.142(d)(10)	(NEW RULE) OSHA requires that privies and toilet rooms shall be cleaned daily

Laundry, handwashing, and bathing facilities	1910.142(f)(1) & 1910.142(f)(2)	(CHANGE) OSHA changes the number of wash basins from 1 for every 15 persons (per ETA) to 1 for every 6 persons. Shower heads also increase from 1 to every 15 persons (per ETA) to 1 every 10 persons. Floors shall be impervious to moisture AND OSHA includes laundry rooms to include floor drains. All junctions of the curbing and the floor shall be covered. The walls and partitions of shower rooms shall be smooth and impervious to the height of splash.
Laundry, handwashing, and bathing facilities	1910.142(f)(1)(iv) & 1910.142(f)(3)	(NEW RULE) OSHA requires a slop sink in each building used for laundry, hand washing, and bathing. Heating water shall be provided (CHANGE) OSHA requires every service building shall be provided with equipment capable of maintaining a temperature of at least 70 deg. F. during cold weather
Laundry, handwashing, and bathing facilities	1910.142(f)(4)	
Laundry, handwashing, and bathing facilities	1910.142(f)(5)	(NEW RULE) OSHA mandates facility for drying clothes shall be provided
Lighting	1910.142(g)	(CHANGE) OSHA requires at least one ceiling-type light fixture and Light levels in toilet and storage rooms shall be at least 20 foot-candles 30 inches from the floor. Other rooms, including kitchens and living quarters, shall be at least 30 foot-candles 30 inches from the floor.
Refuse Disposal	1910.142(h)(1)	(CHANGE) OSHA mandates single service containers, approved by the appropriate health authority shall be provided for the storage of garbage AND shall be located within 100 feet of each shelter on a wooden, metal, or concrete stand.
Construction and operation of kitchens, dining hall, and feeding facilities	1910.142(i)(1)	(NEW RULE) OSHA requires In all camps where central dining or multiple family feeding operations are permitted or provided, the food handling facilities shall comply with the requirements of the "Food Service Sanitation Ordinance and Code," Part V of the "Food Service Sanitation Manual," U.S. Public Health Service Publication 934 (1965), which is incorporated by reference as specified in Sec. 1910.6.
Construction and operation of kitchens, dining hall, ar	1910.142(i)(2)	(CHANGE) OSHA states that There shall be no direct opening from living or sleeping quarters into a kitchen or dining hall.
Construction and operation of kitchens, dining hall, and feeding facilities	1910.142(i)(3)	(NEW RULE) OSHA requires No person with any communicable disease shall be employed or permitted to work in the preparation, cooking, serving, or other handling of food, foodstuffs, or materials used therein, in any kitchen or dining room operated in connection with a camp or regularly used by persons living in a camp.
First Aid	1910.142(k)(1) & 1910.142(k)(2)	(NEW RULES) OSHA states Adequate first aid facilities approved by a health authority shall be maintained and made available in every labor camp for the emergency treatment of injured persons. AND Such facilities shall be in charge of a person trained to administer first aid and shall be readily accessible for use at all times.
Reporting Communicable Diseases	1910.142(l)(1) & 1910.142(l)(2)	(NEW RULES) OSHA requires that It shall be the duty of the camp superintendent to report immediately to the local health officer the name and address of any individual in the camp known to have or suspected of having a communicable disease. AND Whenever there shall occur in any camp a case of suspected food poisoning or an unusual prevalence of any illness in which fever, diarrhea, sore throat, vomiting, or jaundice is a prominent symptom, it shall be the duty of the camp superintendent to report immediately the existence of the outbreak to the health authority by telegram, telephone, electronic mail or any method that is equally fast.